

RUGGED HANDHELD

Granit 1991iSR Ultra-Rugged Standard Range Scanner

Granit 1991iSR Ultra-Rugged Standard Range Scanner

Overview



Feedback

Ensure maximum productivity and uptime with Granit™ 1991iSR standard range ultra-rugged barcode scanner. Best-in-class durability ensures low TCO. Premium scanning performance ensures even damaged or low quality codes scan quickly. Granit XP expands capabilities and redefines ultra-rugged scanning.

- Built to survive harsh treatment including 3 m (10 ft) drops, 7,000 1 m (3.3 ft) tumbles, operating temperatures from -30°C to 50°C (-22°F to 122°F) and IP67 sealing, Granit XP reduces service costs and increases device uptime.
- Granit provides extreme performance scanning, even on damaged and low-quality barcodes. High-quality barcodes scan and transmit faster than ever.
- The SR model is ideally suited to normal, near-field scanning operations on 1D and 2D barcodes. For longer distances, refer to other models in the Granit family.
- Honeywell Operational Intelligence software delivers on-demand scan insights, enabling higher employee productivity and throughput.
- The Honeywell Scanner Management Utility (SMU) creates a holistic solution that automates how you deploy and update the scanners in your environment.

Following a legacy of successful deployments, the next generation Granit™ XP scanners expand capabilities and redefine ultra-rugged scanning. With a best-in-class 10' drop spec, Granit™ XP is engineered to keep on working after the impact of drops from loading docks, fork trucks, and picking trucks. The 1 meter (3.3 foot) tumble test indicates long term durability with daily knocks and drops from workstation or waist height. A best-in-class 7,000 tumble specification ensures Granit™ scanners will be ready to work for the long term. And IP67 dust and moisture sealing protect scanning performance under harsh treatment. Barcodes make data entry faster and more accurate, maximizing productivity in your operations. However, damaged and low quality barcodes can make transactions slow and painful. Bad labels commonly occur in the warehouse/DC and industrial space due to low quality printing or damage during handling. Granit XP, built on Honeywell's next-generation imaging platform, ensures that otherwise challenging labels do not create a bottleneck in your process. The Granit™ XP 1991iSR model offer high-durability, extreme performance scanning for standard range operations. Created for applications where high speed scanning is needed to maximize productivity, and where durability is non-negotiable for low total cost of ownership, the Granit™ XP 1991iSR scanner offers the optimal solution.

Specifications

DIMENSIONS

Overall Dimensions

- 192 mm x 76 mm x 100 mm
- 7.6 in x 3.0 in x 3.9 in

SCANNING SPECIFICATIONS

Skew

- 65°

Decode Capability

- 1D/2D

Motion Tolerance

- Up to 177 in/s
- Up to 4500 mm/s

Number of Scans

- Up to 50,000 scans per charge

Scanning Range

- Standard range (SR)

Print Contrast

- 20% minimum reflectance difference

Scan Pattern

- Area Imager (1280 x 800NEWLINEpixel array)

Brightness

- 0 to 100,000 lux
- 9,290 foot-candles

Pitch

- 45°

NETWORK

Bluetooth Specifications

- 2.4 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth® v4.2

Bluetooth

- Yes

HARDWARE

Host System Interface

- Keyboard Wedge
- RS-232 TTL
- USB

Wireless

- Class 1: 100 m (330 ft) line of sight

ELECTRICAL

Standby Power

- 0.6 W

ENVIRONMENTAL

Storage Temperature Range

- -40°C to 70°C
- -40°F to 158°F

Operating Humidity

- Up to 95% relative humidity, non-condensing

STANDARDS & APPROVALS

Tumble Specifications

- 7,000 1 m (3.3 ft) tumbles

Drop Specifications

Protection Ratings

- IP65

- 2.4 m (8 ft): 20 drops at 25°C (77°F), 55% RH
- 3 m (10 ft): MIL-STD-810G, 25°C (77°F), 55% RH
- 50 drops from -30°C to 50°C (-22°F to 122°F), uncontrolled RH
- IP67

OTHERS

Operating Power

- 5 W (1000 mA @ 5 VDC)

Input Voltage

- 4.0 VDC to 5.5 VDC

Operating Temperature

- -20°C to 50°C
- -4°F to 122°F

Warranty Duration

- Three-year factory warranty

Brand

- Honeywell

Power Connector Type

- Cordless

Honeywell
Safety and Productivity
Solutions
855 S Mint St
Charlotte, NC 28202
800-582-4263

Granit 1991iSR Ultra-Rugged Standard Range Scanner
© 2023 Honeywell International Inc.
All rights reserved.

Honeywell

Feedback

This document was generated on 2023-10-03 12:52:53 PM (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.