

Texecom Limited Bradwood Court, St. Crispin Way, Haslingden, Great Britain BB4 4PW

Telephone (General) +44 (0)1706 234800

Facsimile (Sales) +44 (0)1706 223450

Email intsales@texe.com

Premier LCD Keypad (DBA-0193)



Features:

- ✓ Premier Elite and Premier Series Compatible
- ✓ 2-line custom alphanumeric display
- ✓ Touchtone Keys
- ✓ Fully Adjustable Backlighting
- √ 2 Additional Zones
- ✓ 1 Programmable Output
- √ Back Tamper
- ✓ LED indications for Armed, Ready, Power, Service and Bypass
- √ Fully addressable with dip switch
- ✓ CE Certified
- ✓ PD6662:2010 Grade 3 Class II







Certificate Number: FM 35285



Texecom Limited Bradwood Court, St. Crispin Way, Haslingden, Great Britain BB4 4PW

Telephone (General) +44 (0)1706 234800

Facsimile (Sales) +44 (0)1706 223450

Email intsales@texe.com

Technical Specifications:

- ✓ Operating Voltage 10 13.9VDC
- ✓ LCD: 10mA-170mA
- ✓ Quiescent (Not Backlit) 45mA
- ✓ Alarm (Not Backlit) 100mA
- ✓ Alarm + Fully Backlit 170mA
- ✓ Network 4-wire standard 7/0.2 alarm cable up to 250m. Star, Daisy Chain or any combination.
- ✓ Premier LCD 32 Character LCD
- ✓ Zones 2
- ✓ Output 100mA switched to 0V
- ✓ Back Lighting Fully Adjustable
- ✓ Speaker Output Minimum Load 8 _ (programmable volume) Maximum Current 325mA.
- ✓ Operating Temperature -10°C (+14°F) to +50°C (+122°F)
- ✓ Storage Temperature -20°C (-4°F) to +60°C (+140°F)
- ✓ Maximum Humidity 95% non-condensing
- ✓ EMC Environment Residential, Commercial, Light Industrial or Industrial.
- ✓ Dimensions 145mm X 115mm X 30mm
- ✓ Packed Weight 260g Approx.





