

Texecom

Designed to Perform

Texecom Limited

Bradwood Court, St. Crispin Way,
Haslingden, Great Britain BB4 4PW

Telephone (General) +44 (0)1706 234800

Facsimile (Sales) +44 (0)1706 223450

Email intsales@texe.com

Wired Shutter Contact (AEF-0004)



Features:

- ✓ High Quality Alloy Finish
- ✓ Double pole/Normally Closed
- ✓ Other resistor value available
- ✓ 45cm Armoured cable length
- ✓ EN50131-2-6 Grade 2
- ✓ Environmental Class III

Technical Specifications:

Specifications			
RS002 Grade 2			
Connections	4 Core x 7/0.2 Copper Cable	Voltage Range	12Vdc
Armoured Cable Length	450mm	Switching Current	500mA @ 12Vdc
Reed Switches	1	Contact Material	Rhodium
Pull-in Gap	50mm	Colours	Aluminium
Material	Aluminium	Tamper	Integrity Loop
Contact Size	175 x 50 x 13mm	Standards	EN50131-2-6 Grade 2
Magnet Size	85 x 70 x 30mm	Environmental Class	III
Contact Form	SPST form A		



Certificate Number: FM 35285

Registered Office: Bradwood Court, St. Crispin Way, Haslingden, Lancs BB4 4PW.
Registered in England No. 2084170