

Non-contact voltage tester

testo 745

Filter for high-frequency interference signals

Adjustable sensitivity

Visual and acoustic signal

Waterproof and dustproof according to IP 67

Measuring point illumination



The testo 745 non-contact voltage tester with a voltage range of up to 1,000 V AC is particularly well-suited to fast initial checking of any suspected fault sources. When the presence of alternating current is determined, the testo 745 gives a warning via a clear visual and acoustic signal.

In order to increase reliability, the voltage tester has a filter for high-frequency interference signals and is also waterproof and dustproof according to IP 67.

Technical data/accessories

testo 745

testo 745, non-contact voltage tester
including batteries

Order no. 0590 7450



Technical data

Voltage testing	12 to 1,000 V AC
Measuring point illumination	✓
Measurement category	CAT IV 600 V CAT III 1,000 V
Protection class	IP 67
Operating temperature	-10 to +50 °C
Storage temperature	-15 to +60 °C
Dimensions	155 x 25 x 23 mm (L x W x H)
Weight	63 g
Warranty	2 years
Authorizations	CSA, CE
Standards	EN 61326-1, EN 61010-1

1981 1514/cw/01.2016

Subject to change, including technical modifications, without notice.

Accessories

Order no.

ISO calibration certificate voltage tester	0520 0750	
DAkkS calibration certificate voltage tester	0520 0751	

Testo India Pvt Ltd

Head Office:

Plot No. 23, Sindh Society, Baner Road,
Aundh, Pune - 411007, Maharashtra, India
Tel: +91 20 6560 0203 | Fax: +91 20 2585 0080
Email: info@testoindia.com | Web: www.testo.in

Regional Offices / Representatives:

Ahmedabad | Baroda | Bengaluru | Chandigarh | Chennai | Guwahati
Hyderabad | Indore | Kolkata | Lucknow | Mumbai | New Delhi | Raipur

Authorized Channel Partner